

*Epson Professional Media*

# CrystalClear® Film

Epson Professional Imaging is pleased to announce the launch of CrystaClear® Film. This optically clear polyester film is engineered to provide the highest image quality, performance and accuracy required for clear overlay and color key applications. As an ideal component for the Epson Stylus® Pro 7900 and 9900 Proofing Edition Printers with Epson UltraChrome® HDR Ink, this media provides a quick drying, smooth surface with the sharpness and precision that defines Epson's professional proofing solutions.

Optimized for Epson UltraChrome K3® Ink and Epson UltraChrome HDR Ink, this media delivers outstanding accuracy and short-term stability.

## Features/Benefits

- Glossy finish
- 4.5 mil
- Fast drying
- Ideal for progressives



## Technical Specifications

| Basis Weight         | Thickness | Opacity | Base Material | Surface Finish | Core | Spindle |
|----------------------|-----------|---------|---------------|----------------|------|---------|
| 150 g/m <sup>2</sup> | 4.5 mil   | 11%     | Polyester     | Gloss          | 3"   | 3"      |

## Ordering Specifications

| Single Carton Product Code | Roll Size/Sheet Count | W x D x H           | Weight  | UPC Code        |
|----------------------------|-----------------------|---------------------|---------|-----------------|
| S045151                    | 17" x 100'            | 19.0" x 4.9" x 4.9" | 7.5 lb  | 0 10343 87426 8 |
| S045152                    | 24" x 100'            | 26.0" x 4.9" x 4.9" | 10.5 lb | 0 10343 87427 5 |
| S045153                    | 44" x 100'            | 46" x 4.9" x 4.9"   | 19.3 lb | 0 10343 87428 2 |

  

| Master Carton Product Code | Roll Size/Sheet Count | W x D x H             | Weight  | UPC Code          |
|----------------------------|-----------------------|-----------------------|---------|-------------------|
| S045151                    | 17" x 100'            | 19.5" x 10.0" x 10.0" | 40.0 lb | 200 10343 87426 2 |
| S045152                    | 24" x 100'            | 26.8" x 10.0" x 10.0" | 45.1 lb | 200 10343 87427 9 |
| S045153                    | 44" x 100'            | 46.5" x 10.0" x 5.4"  | 41.3 lb | 200 10343 87428 6 |

## Operating Specifications

Required temperature for optimum performance 68 ° to 77 °F  
20 ° to 25 °C

Required humidity for optimum performance 40 – 60% RH  
(Note: High humidity will prolong the drying time for lamination purposes.)

### Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

### Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Since all dyes, pigments and paper change over time, Epson does not warrant this product against color changes and fading. Epson's liability for any defects in manufacturing and packaging is limited to the replacement cost of the product. Specifications are subject to change without notice. Epson, Epson Stylus, Epson UltraChrome and Epson UltraChrome K3 are registered trademarks and Epson Exceed Your Vision is a registered logomark of Seiko Epson Corporation. © Copyright 2009 Epson America, Inc. CPD-30720 7/09 PDF